671.821 JUN 9 1930 "AW." Standard Diamond FLOOR PLATES (ACTUALSIZE) TRACE AW MARK NSHOHOCKET!



Boiler Room



Standard "A.W." Diamond Railroad Crossing

"A. W." PRODUCTS"

"SWEDE" PIG IRON BASIC AND ALL FOUNDRY GRADES

BILLETS, BLOOMS, SLABS CARBON AND ALLOY STEEL

SHEARED STEEL PLATES

BLUE ANNEALED SHEETS

ROLLED STEEL FLOOR PLATES DIAMOND, DIAMONDETTE, RIBBED, TRAFFIC TREADS

Alan Wood Steel Company CONSHONCKEN, PA.

DISTRICT OFFICES

August 15, 1929



Standard "A.W." Diamond Car Vestibule Floor



"A.W." Diamondette Car Vestibule Floor

Standard "A. W." Diamond

-1" to 1" inclusive

FEATURES

The design of the STANDARD "A.W." Diamond Pattern Floor Plate was scientifically developed to produce the most efficient anti-slip surface with proper consideration given to the effect of attrition in use.

The raised, oval, bevelled edge of the distinctive pattern provides traction around its entire circumference, and affords a firm foothold.


The open design of the patterned area prevents water, dirt, or refuse from permanently lodging on the plate, which is self-draining.

The uniformity of the pattern admits properly matching and presents a neat and attractive appearance, pleasing to the eye and harmonious in effect with any architectural design.

USES

"A.W." FLOOR PLATES are used in all step, flooring, platform, runway, trench-cover, and modern engineering and construction work generally.

Samples and all engineering information sent on request,



Standard "A.W." Diamond Cellar Door



Standard "A.W." Diamond Scale Platform

"A. W." Diamondette Pattern

No. 16 to 12 Gauge

"A.W." DIAMONDETTE Pattern Floor Plates offer a lighter section with a proportionate saving in weight, embodying the same scientific features of the "A.W." STANDARD Pattern, but providing a greater area of patterned surface, and affording greater strength than a plain section of corresponding gauge or thickness.

For automobile running boards, step-plates, floor boards, locomotive step-plates, vestibule platforms, aisleways, cover plates, and all places requiring a raised anti-slip surface without the necessity of providing earrying capacity in the plate itself, the "A.W." DIAMONDETTE Floor Plates are decidedly advantageous.

Samples and all Engineering Information on Request

"A. W." Traffic Treads

STANDARD "A.W." Floor Plates when used for vehicular runways on wooden bridge floors, platform scales, etc., are designated as "A.W." TRAFFIC TREADS. Detailed folder furnished on request.



WIDTH AS ROLLED

STANDARD "A.W." DIAMOND

(Full Size)

Length of diamond will run parallel to length as rolled. In specifying directions in which diamonds are desired to run, please note limits of width as rolled, shown on page 13.



WIDTH AS ROLLES

"A.W." DIAMONDETTE


Full Size

No. 16 to 12 Gauge

Length of diamond will run parallel to length as rolled. In specifying directions in which diamonds are desired to run, please note limits of width as rolled, shown on page 13.



"A.W." Diamondette Motor Bus Tread



"A.W." Diamondette Automobile Running Board

Schedule of Extras

STANDARD "A.W." DIAMOND AND "A.W." DIAMONDETTE

WIDTH
Extra per 100 lbs
24" and wider Base
Under 24 to 12" add 10c
Under 12 to 6"add 20c
200
T. P. N. C. WITT
LENGTH
60" and longer Base
Under 60 to 30" add 10c
Under 30 to 18"
QUALITY
Extra par
Copper Bearing Steel (minimum.
.20 copper)add 15c
THICKNESS
Standard "A.W." Diamond
EAO A DIA
3/16" and heavier Base
1 add 20e
"A.W." Diamondette
Extra per
No. 12 Gauge Base
No. 14 " 50e
No. 16 \$1.00



AP | Discussion



Section County

Sizes and Weights

"A.W." STANDARD

Thickness	1/8"	3/16"	1/4"	546"	3/8"	1/2"	5/8"	3/4"
Width			I	ENGT	H IN	INCH	ES	
20"	240	300	300	300	300	300	300	300
24"	240	300	300	300	300	300	300	300
30"	240	300	300	300	300	300	300	300
36"	240	300	300	300	300	300	300	300
40"	240	300	300	300	300	300	300	300
44"	240	300	300	300	300	300	300	300
48"	240	300	300	300	300	300	300	300
52"	240	300	300	300	300	300	300	300
56"	240	300	300	300	300	300	300	300
60"	240	300	300	300	300	300	300	300
66"			240	240	240	240	240	240
72"					240	240	240	240

WEIGHTS PER SQUARE FOOT

Thickness	"A.W." DIA	MOND
35"	7.75 11	bs.
3/16"	8.75	6.4
34"	11.25	i.i.
5,10"	13.75	6.0
3/8"	16.25	6.
F_"	21.5	
5/8"	26.5	**
34"	31.75	4+

"A.W." DIAMONDETTE

0			W 1. C
No. 12		Maximum Size 24" x 192"	Weight per sq. ft. 5.5 lbs.
110. 14	\	or	0.5 108.
No. 14	l	36" x 144"	3.5 lbs.
No. 16		30" x 96"	2.875 lbs.

The weights shown above are approximate only, and may vary according to the size of the plate. Thickness is measured through body of plate, i. e., exclusive of pattern.



"A.W." Diamondette Tank Car Running Board



"A.W." Diamondette Auto Truck Running Board

Shearing

Regular Mill Shearing. "A.W." Rolled Steel Floor Plates are furnished subject to the usual variations in rolling and shearing incident to regular mill practice, variation being over the sizes specified. The amount of variation depends upon thickness, width and length.

When so specified on order, the variation in shearing may be kept under rather than over.

Extra for Special Shearing. Shearing variations may be minimized by "Special Shearing" (sometimes called "Resquaring") at 10 cents per 100 pounds extra-

"Special Sheared" Floor Plates are furnished in normal sizes with a total variation of 40, which may be over or under, as preferred, or from 40 over to 17 under, making total of 40. These variations are based on normal dimensions and may be exceeded depending on width, length and thickness.

Fabrication

All types of Special Forming, Bending, Punching, Countersinking, In-cutting, Circular Cutting, etc., quoted on application, accompanied by blue-print and details.

On request we will gladly furnish a graphic chart showing deflections and safe loads of our "AW," Diamond Pattern Floor Plates

